



EPC-R33 Series Rack Online UPS 30-40kVA

MODEL		EPC-R33030CL	EPC-R33040CL
Power Rating		30KVA/30KW	40KVA/40KW
Input	Rated Voltage	380VAC ~ 415VAC	
	Rated Frequency	50/60Hz (Configurable)	
	Power Factor	>0.99	
Bypass	Rated Voltage	380VAC ~ 415VAC	
	Rated Frequency	50/60Hz (Configurable)	
	Bypass Overload	125%, Long time;130%,10mins;150%,1min;>150%,1s	
Output	Rated Voltage	380VAC ~ 415VAC	
	Rated Frequency	50/60Hz (Configurable)	
	Output PF	1	
	Inverter Overload	110% for 1 hour;125% for 10 min;150% for 1min;>150% for 200ms	
Battery	Voltage	±240VDC	
	Efficiency	AC Mode: 96.0%max Battery Mode: 95.5%max	
System	Display	LED + LCD + Touch Screen	
	Interface	USB, RS485, Programmable dry contact	
	Option	SNMP, parallel kit, LBS, RS232	
	Temperature	Operation: 0 ~ 40 °C Storage: -40~70°C	
Physical	Dimension W*D*H (mm)	438*700*174	
	Weigh (kg)	41	