


EPC-iSmart Series Integrated Cabinet Solution

System	IT rated power	3kVA	
	Mains	220Vac,50Hz/60Hz	
	Ambient temperature	0-45°C	
	Ambient humidity	10-95% (Relative humidity)	
	IP Class	IP5X	
	Altitude	1000m, decreasing for >1000m	
Cabinet	Dimension*D*H)	600*1200*2000mm (Without caster)	
	Space occupation	≤32U	
	Display	10.1" touch screen LCD	
	Ambient Light	Front RGB three-color ambient light	
	Lighting method	Front and rear LED	
	Cable entry	Top and bottom	
	Access control system	Fingerprint + swipe card (IC&ID) + digital password three in one	
Power Supply and Distribution System	Distribution module	Configuration	Main CB : 63A/2P, rack installation, with the indicator of operation
		Lightning protection	Class C lightning protection (Standard for 2P, optional for 1P+N)
		Height	3U
	UPS	Capacity	3kVA/6kVA
		Power distribution	Single phase-in and single phase-out
		Battery	Built-in battery or external battery cabinet
	PDU	Normal type	IEC C13*2pcs, 16 ports (13*10A+3*16A)
		Intelligent type	Optional for 24 ports
Monitoring System	Supervision system	Intelligent integrated monitoring host	
	Single cabinet	Single cabinet control module	
	Environment monitoring	smoke detector*1	
		Temperature & humidity detector*1	
		Water leakage detector*1	
		Webcam (optional)	
		Infrared detector (optional)	
	Other detector	SMS alarm (optional)	
Emergency Ventilation	Emergency measures	Emergency pop-up door system	
Cooling System	Air conditioner	Rack type (Standard for constant temperature)	
	Rated cooling capacity	3.7kW	
	Rated power consumption	1.2kW	
	Rated air volume	700m³/h	
	Drop height	-5m≤ΔH≤10m	
Physical	Package dimensions	720*1338*2230mm	
	Weight	188kg (without AC, UPS, battery pack)	
	Cabinet color	Black (RAL9004)	